Technical specifications

Cloudscape carpet tiles meet the requirements of EN 1307

tessera® cloudscape

	Description		Tufted multi-pile height loop carpet tile
•	Dimensions		50cm x 50cm
(° ×)	Total thickness		7.2mm ± 10%
	Pile height		4.4mm ± 0.5mm
	Collection size		16 colourways, 4m² per box
	Application	EN 1307	Class 33, Suitable for any type of heavy contract application
	Pile composition		100% polyamide 6
	Dye method		100% solution dyed
	Tuft density		217,267 per m² ± 10%
R	Pile weight		665 gsm ± 10%
	Total weight		4,180 gsm ± 10%
	Primary backing		Polyester
	Secondary backing		ProBac recycled mineral filler with low amount of modified bitumen, and polyester fleece. Contains over 76% recycled content
	Castor chair use	BS EN 985	Minimum R value: ≥2.4
7	Light fastness	BS EN ISO 105 B02	≥5
	Impact sound reduction	ISO 10140-3	$\Delta L_{W} = 26 \text{ dB}$
	Creating Better Environments		
Ť	Renewable Energy		All Tessera carpet tiles are manufactured using 100% renewable energy (electricity & biogas)
O	Recycled Content		Cloudscape carpet tiles contain 62% recycled content by weight
1	Indoor Air Quality		Cloudscape carpet tiles comply to 01350 Indoor Air Quality standard
hack to the floor mapping total rickoring	Back to the Floor		Installation off cuts can be collected via Back to the Floor
_	Ska		Cloudscape meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes
<u>10</u>	Guarantee		Cloudscape carpet tiles are guaranteed for 10 years under heavy contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.
\bigoplus	Installation method		Non-directional or monolithic
	Cloudscape carpet tiles meet the requirements		s of EN 14041 EN 14041
B _{II} -s1	Reaction to fire	EN 13501-1	B _{fl} -s1
975	Slip resistance	EN 13893	DS: ≥0.30
F	Electrical resistance	BS ISO 10965 & EN1815	$<$ 1 x 10 $^9\Omega$: Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

Our recommended adhesive for our collection of Tessera carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Cloudscape carpet tiles are manufactured in a facility certified to SA8000® and OHSAS 18001.

The Life Cycle Assessment (LCA) of Cloudscape is documented in an Environmental Product Declaration (EPD). Cloudscape is currently under assessment for the BREEAM building rating scheme.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.





www.forbo-flooring.co.uk

